

Hőmérséklet távadó WiFi interfésszel, 1 Pt1000 hőérzékelő csatlakozással

Termékkód: W0711



WiFi interfésszel rendelkező hőmérséklet távadó, egy Pt1000 hőérzékelő csatlakozással (az érzékelő külön rendelendő).

Communication with the sensor is done via a wireless WiFi network. The device allows sending measured values to the online [COMET Cloud](#) or [COMET Database](#) storage with the shortest interval of 5 minutes. The values can be displayed on integrated web pages and provided to third party systems using the Modbus TCP protocol. The measured values are displayed on the LCD display.

The device continuously evaluates the alarm limits of the measured values and in case of exceeding them, it can send an e-mail or inform by means of acoustic or optical signaling. Two alarm limits are supported for each measurement channel.

The main advantage of sensors with WiFi interface is the simplicity of deployment in places where WiFi infrastructure is already available. Just place the sensor in the desired location and connect it to the WiFi network. WiFi sensor in conjunction with [COMET Cloud](#) or [COMET Database](#) offers a comprehensive solution for monitoring and alarm without the need for a server solution on the part of the user. If necessary, however, the sensor can also be connected to third-party systems, either using the Modbus TCP protocol or by sending JSON data to an http server.

Thanks to these unique features, the WiFi sensor will find applications and a wide range of application areas.

Műszaki adatok

| | |
|--------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| TEMPERATURE SENSOR - external probe Pt1000 | |
| Measuring range | -90 to +260 °C |
| Accuracy | ±0.2 °C in the range -90 to +100 °C; ±0.2 % from reading from +100 to +260 °C |
| Resolution | 0.1 °C |
| GENERAL TECHNICAL DATA | |
| Operating temperature | -30 to +60 °C |
| Channels | 1x external temperature probe (Pt1000), CINCH connector |
| Measuring interval | 1 s |
| Sending interval to COMET Cloud | adjustable 5 minutes to 12 hours |
| Communication protocols | HTTP(S), SMTP, ModbusTCP, HTTP POST |
| Alarm signalization | e-mail, acoustic, LED |
| Power | 5.0 to 5.4 VDC; consumption 300 mA (max. 500 mA); USB-C connector |
| Radio section | frequency: 2.4 GHz; max. transmit power: 18 dBm; standard: 802.11 b/g/n; contain CC3220MODSF with FCC ID: Z64-CC3220MOD |

| | |
|------------------|-----------------|
| Protection class | IP30 |
| Dimensions | 81 x 93 x 32 mm |
| Weight | 115 g |
| Warranty | 3 years |